

# Aer conditionat Nyoko - SRK45ZSP-W / SRC45ZSP- W



Capacitate nominala de racire: 4.5 kW

## Poze unitate interna si unitate externa



## Specificatii

Unitate interna			SRK45ZSP-W	
Unitate externa			SRC45ZSP-W	
Sursa de putere			Monofazic, 220 - 240V, 50Hz	
Capacitate nominala de racire (Min~Max)		kW	4.5(1.3~4.8)	
Capacitate nominala de incalzire (Min~Max)		kW	5.0(1.2~5.8)	
Consumul de energie	Racire/Incalzire	kW	1.350 / 1.360	
EER/COP	Racire/Incalzire		3.33 / 3.68	
Amperaj maxim		A	14.5	
Nivel putere sonora	Unitate interna	Racire/Incalzire	dB(A)	56 / 62

Unitate externa	Racire/Incalzire		63 / 64	
Nivel presiune sonora	Unitate interna	Racire (Hi/Me/Lo/Ulo)	44 / 39 / 24	
		Incalzire (Hi/Me/Lo/Ulo)	48 / 41 / 30	
	Unitate externa	Racire/Incalzire	51 / 51	
Flux de aer	Unitate interna	Racire (Hi/Me/Lo/Ulo)	m <sup>3</sup> /min	9.0 / 7.2 / 3.8
		Incalzire (Hi/Me/Lo/Ulo)		12.0 / 9.2 / 6.2
	Unitate externa	Racire/Incalzire		35.6 / 33.4
Dimensiuni exterioare	Unitate interna	Inaltime x Latime x Adancime	mm	267 x 783 x 210
	Unitate externa			595 x 780(+62) x 290
Greutate neta	Unitate interna / Unitate externa		kg	7.5 / 36.0
Refrigerant		Tip/GWP		R32 / 675
Refrigerant		Incarcare	kg/TCO <sub>2</sub> Eq	1.10 / 0.743
Dimensiuni teava refrigerant		Lichid/Gaz	ø mm	6.35(1/4") / 12.7(1/2")
Lungime teava refrigerant (o directie)			m	Max. 25
Diferente de nivel suportate		Unitate externa este mai sus/mai jos	m	Max. 15 / Max. 15
Unitate externa operating temperature range		Racire	°C	-15~46
		Incalzire		-15~24
Filtre				-
Clasa energetica (Racire/Incalzire)				A++/A+
SEER				6.30
SCOP (Climat temperat)				4.20
Pdesign (Racire/Incalzire(@-10°C))			kW	4.50/3.80