

# Aer conditionat Nyoko - SRK25ZSP-W / SRC25ZSP- W



Capacitate nominala de racire: **2.5 KW**

## Poze unitate interna si unitate externa



## Specificatii

Unitate interna			SRK25ZSP-W	
Unitate externa			SRC25ZSP-W	
Sursa de putere			Monofazic, 220 - 240, 50Hz	
Capacitate nominala de racire (Min~Max)		kW	2.5(0.9~3.1)	
Capacitate nominala de incalzire (Min~Max)		kW	2.8(1.0~4.1)	
Consumul de energie	Racire/Incalzire	kW	0.710 / 0.690	
EER/COP	Racire/Incalzire		3.52/4.05	
Amperaj maxim		A	9	
Nivel putere sonora	Unitate interna	Racire/Incalzire	dB(A)	57 / 57

Unitate externa	Racire/Incalzire		57 / 56	
Nivel presiune sonora	Unitate interna	Racire (Hi/Me/Lo/Ulo)	45 / 34 / 23	
		Incalzire (Hi/Me/Lo/Ulo)	43 / 34 / 26	
	Unitate externa	Racire/Incalzire	47 / 45	
Flux de aer	Unitate interna	Racire (Hi/Me/Lo/Ulo)	m <sup>3</sup> /min	10.0 / 7.3 / 4.2
		Incalzire (Hi/Me/Lo/Ulo)		9.5 / 7.3 / 5.2
	Unitate externa	Racire/Incalzire		23.7 / 19.7
Dimensiuni exterioare	Unitate interna	Inaltime x Latime x Adancime	mm	267 x 783 x 210
	Unitate externa			540 x 645(+57) x 275
Greutate neta	Unitate interna / Unitate externa		kg	7.0 / 26.5
Refrigerant		Tip/GWP		R32 / 675
Refrigerant		Incarcare	kg/TCO <sub>2</sub> Eq	0.550 / 0.371
Dimensiuni teava refrigerant		Lichid/Gaz	ø mm	6.35(1/4") / 9.52(3/8")
Lungime teava refrigerant (o directie)			m	Max. 15
Diferente de nivel suportate		Unitate externa este mai sus/mai jos	m	Max. 10 / Max. 10
Unitate externa operating temperature range		Racire	°C	-15~46
		Incalzire		-15~24
Filtre				-
Clasa energetica (Racire/Incalzire)				A++/A+
SEER				6.80
SCOP (Climat temperat)				4.10
Pdesign (Racire/Incalzire(@-10°C))			kW	2.50/2.80