

Aer conditionat Harukaze Pro - SRK35ZSX-W / SRC35ZSX-W



Capacitate nominala de racire: **3.5 KW**

Poze unitate interna si unitate externa



Specificatii

Unitate interna			SRK35ZSX-W	
Unitate externa			SRC35ZSX-W	
Sursa de putere			Monofazic, 220 - 240, 50Hz	
Capacitate nominala de racire (Min~Max)		kW	3.5 (0.9~4.5)	
Capacitate nominala de incalzire (Min~Max)		kW	4.3 (0.8~6.8)	
Consumul de energie	Racire/Incalzire	kW	0.74 / 0.90	
EER/COP	Racire/Incalzire		4.73 / 4.78	
Amperaj maxim		A	9	
Nivel putere sonora	Unitate interna	Racire/Incalzire	dB(A)	58 / 58

Unitate externa	Racire/Incalzire		61 / 62	
Nivel presiune sonora	Unitate interna	Racire (Hi/Me/Lo/Ulo)	43 / 35 / 26 / 19	
		Incalzire (Hi/Me/Lo/Ulo)	42 / 35 / 28 / 19	
	Unitate externa	Racire/Incalzire	48 / 47	
Flux de aer	Unitate interna	Racire (Hi/Me/Lo/Ulo)	m ³ /min	13.1 / 10.8 / 7.3 / 5.0
		Incalzire (Hi/Me/Lo/Ulo)		13.9 / 11.8 / 8.6 / 5.4
	Unitate externa	Racire/Incalzire		36.0 / 31.0
Dimensiuni exterioare	Unitate interna	Inaltime x Latime x Adancime	mm	305 x 920 x 220
	Unitate externa			640 x 800(+71) x 290
Greutate neta	Unitate interna / Unitate externa		kg	13.0 / 43.0
Refrigerant		Tip/GWP		R32 / 675
Refrigerant		Incarcare	kg/TCO ₂ Eq	1.20 / 0.810
Dimensiuni teava refrigerant		Lichid/Gaz	ø mm	6.35(1/4") / 9.52(3/8")
Lungime teava refrigerant (o directie)			m	Max.25
Diferente de nivel suportate		Unitate externa este mai sus/mai jos	m	Max.15 / Max.15
Unitate externa operating temperature range		Racire	°C	-15~46
		Incalzire		-20~24
Filtre				Filtru Antialergeni x 1, Filtru lavabil fotocatalitic si dezodorizant x 1
Clasa energetica (Racire/Incalzire)				A+++ / A+++
SEER				9.50
SCOP (Climat temperat)				5.10