

# Aer conditionat Harukaze SRK35ZS-WB / SRC35ZS-W

Capacitate nominala de racire: 3.5 kW



## Poze unitate interna si unitate externa



## Specificatii

Unitate interna		SRK35ZS-WB		
Unitate externa		SRC35ZS-W		
Sursa de putere		Monofazic, 220 - 240, 50Hz		
Capacitate nominala de racire (Min~Max)		kW	3.5(0.9~4.0)	
Capacitate nominala de incalzire (Min~Max)		kW	4.0(0.9~5.0)	
Consumul de energie	Racire/Incalzire	kW	0.89 / 0.94	
EER/COP	Racire/Incalzire		3.93 / 4.26	
Amperaj maxim		A	9	
Nivel putere sonora	Unitate interna	Racire/Incalzire	dB(A)	54 / 56

Unitate externa	Racire/Incalzire	61 / 61		
Nivel presiune sonora	Unitate interna	Racire (Hi/Me/Lo/Ulo)	40 / 30 / 26 / 19	
		Incalzire (Hi/Me/Lo/Ulo)	41 / 36 / 25 / 19	
	Unitate externa	Racire/Incalzire	50 / 48	
Flux de aer	Unitate interna	Racire (Hi/Me/Lo/Ulo)	m <sup>3</sup> /min	11.3 / 8.7 / 7.0 / 5.0
		Incalzire (Hi/Me/Lo/Ulo)		12.3 / 11.0 / 7.0 / 5.6
	Unitate externa	Racire/Incalzire		31.5 / 27.8
Dimensiuni exterioare	Unitate interna	Inaltime x Latime x Adancime	mm	290 x 870 x 230
	Unitate externa			540 x 780(+62) x 290
Greutate neta	Unitate interna / Unitate externa		kg	9.5 / 34.5
Refrigerant		Tip/GWP		R32 / 675
Refrigerant		Incarcare	kg/TCO <sub>2</sub> Eq	0.78 / 0.527
Dimensiuni teava refrigerant		Lichid/Gaz	ø mm	6.35(1/4") / 9.52(3/8")
Lungime teava refrigerant (o directie)			m	Max. 20
Diferente de nivel suportate		Unitate externa este mai sus/mai jos	m	Max. 10 / Max. 10
Unitate externa operating temperature range		Racire	°C	-15~46
		Incalzire		-15~24
Filtre				Filtru Antialergeni x 1, Filtru lavabil fotocatalitic si dezodorizant x 1
Clasa energetica (Racire/Incalzire)				A++/A++
SEER				8.40
SCOP (Climat temperat)				4.70