

Aer conditionat Nyoko - SRK35ZSP-W / SRC35ZSP- W



Capacitate nominala de racire: **3.2 KW**

Poze unitate interna si unitate externa



Specificatii

Unitate interna			SRK35ZSP-W	
Unitate externa			SRC35ZSP-W	
Sursa de putere			Monofazic, 220 - 240V, 50Hz	
Capacitate nominala de racire (Min~Max)		kW	3.2(0.9~3.7)	
Capacitate nominala de incalzire (Min~Max)		kW	3.6(1.0~4.6)	
Consumul de energie	Racire/Incalzire	kW	0.910 / 0.930	
EER/COP	Racire/Incalzire		3.52 / 3.87	
Amperaj maxim		A	9	
Nivel putere sonora	Unitate interna	Racire/Incalzire	dB(A)	58 / 58

Unitate externa	Racire/Incalzire		59 / 60	
Nivel presiune sonora	Unitate interna	Racire (Hi/Me/Lo/Ulo)	45 / 36 / 23	
		Incalzire (Hi/Me/Lo/Ulo)	44 / 36 / 28	
	Unitate externa	Racire/Incalzire	48 / 48	
Flux de aer	Unitate interna	Racire (Hi/Me/Lo/Ulo)	m ³ /min	9.5 / 6.8 / 4.2
		Incalzire (Hi/Me/Lo/Ulo)		9.6 / 7.4 / 5.5
	Unitate externa	Racire/Incalzire		22.8 / 22.0
Dimensiuni exterioare	Unitate interna	Inaltime x Latime x Adancime	mm	267 x 783 x 210
	Unitate externa			540 x 645(+57) x 275
Greutate neta	Unitate interna / Unitate externa		kg	7.0 / 28.5
Refrigerant		Tip/GWP		R32 / 675
Refrigerant		Incarcare	kg/TCO ₂ Eq	0.68 / 0.459
Dimensiuni teava refrigerant		Lichid/Gaz	ø mm	6.35(1/4") / 9.52(3/8")
Lungime teava refrigerant (o directie)			m	Max. 15
Diferente de nivel suportate		Unitate externa este mai sus/mai jos	m	Max. 10 / Max. 10
Unitate externa operating temperature range		Racire	°C	-15~46
		Incalzire		??-15~24
Filtre				-
Clasa energetica (Racire/Incalzire)				A++/A+
SEER				7.30
SCOP (Climat temperat)				4.40
Pdesign (Racire/Incalzire(@-10°C))			kW	3.20/3.00