




The IP40 protected decorative enclosures are available in sizes from 8 to 72M. They provide superior aesthetic integration. They are available with smoked transparent doors or with blank doors that can be equipped with safety lock, characterized by the "PUSH" opening and closing. They can be equipped with bipolar and unipolar terminal blocks, 80 A and 125 A, with screw wiring; they allow to create simple and neat wiring reducing the set-up time of the enclosure.

| | | | |
|---|--|---|--|
| Clasă izolație | II (conform standardelor IEC 61140) | Culoare | Alb RAL 9016 |
| Dim. exterioare LxHxP (mm) | 400x400x130 | Clasă de protecție IP | IP40 |
| Putere disipabilă (W) | 45 | Cod IK | IK08 |
| Tensiune nominală | 400 V | Culoare ușă | Transparent fumuriu |
| Nr. module EN 50022 | 36 (18x2) | Curent nominal | 125 A |
| Glow Test conductori | 650 °C | Temperatură de operare | -25 +60 °C |
| Tip de material | Fără halogen conform EN 60754-2 | Electrocod | 0321 |
| Termo-presiune cu bilă | 70 °C | Accesorii pentru restabilirea izolației | Capete de șuruburi (GW44623) sau console de fixare în rășină (GW44621) |
| Standard | EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49 | Tensiune izolație | 750 V |
| Nr. maxim blocuri terminale instalabile | 2 x18 module | | |



DIMENSIONAL

TECHNICAL SYMBOLOGY



IP

IP40

IK

IK08


GWT

650 °C



HF

Fără halogen conform EN 60754-2



STANDARDS/APPROVALS

