

Aer conditionat Harukaze Pro - SRK25ZSX-W / SRC25ZSX-W



Capacitate nominala de racire: 2.5 KW

Poze unitate interna si unitate externa



Specificatii

Unitate interna		SRK25ZSX-W		
Unitate externa		SRC25ZSX-W		
Sursa de putere		Monofazic, 220 - 240, 50Hz		
Capacitate nominala de racire (Min~Max)		kW	2.5 (0.9~3.8)	
Capacitate nominala de incalzire (Min~Max)		kW	3.2 (0.8~6.0)	
Consumul de energie	Racire/Incalzire	kW	0.44 / 0.59	
EER/COP	Racire/Incalzire		5.68 / 5.42	
Amperaj maxim		A	9	
Nivel putere sonora	Unitate interna	Racire/Incalzire	dB(A)	55 / 56

Unitate externa	Racire/Incalzire		57 / 58	
Nivel presiune sonora	Unitate interna	Racire (Hi/Me/Lo/Ulo)	39 / 33 / 25 / 19	
		Incalzire (Hi/Me/Lo/Ulo)	40 / 34 / 27 / 19	
	Unitate externa	Racire/Incalzire	44 / 45	
Flux de aer	Unitate interna	Racire (Hi/Me/Lo/Ulo)	m ³ /min	12.2 / 10.0 / 6.7 / 5.0
		Incalzire (Hi/Me/Lo/Ulo)		12.8 / 11.0 / 7.8 / 5.4
	Unitate externa	Racire/Incalzire		31.0 / 31.0
Dimensiuni exterioare	Unitate interna	Inaltime x Latime x Adancime	mm	305 x 920 x 220
	Unitate externa			640 x 800(+71) x 290
Greutate neta	Unitate interna / Unitate externa		kg	13.0 / 43.0
Refrigerant		Tip/GWP		R32 / 675
Refrigerant		Incarcare	kg/TCO ₂ Eq	1.20 / 0.810
Dimensiuni teava refrigerant		Lichid/Gaz	ø mm	6.35(1/4") / 9.52(3/8")
Lungime teava refrigerant (o directie)			m	Max.25
Diferente de nivel suportate		Unitate externa este mai sus/mai jos	m	Max.15 / Max. 15
Unitate externa operating temperature range		Racire	°C	-15~46
		Incalzire		-20~24
Filtre				Filtru Antialergeni x 1, Filtru lavabil fotocatalitic si dezodorizant x 1
Clasa energetica (Racire/Incalzire)				A+++ / A+++
SEER				10.30
SCOP (Climat temperat)				5.20