

Aer conditionat Harukaze SRK25ZS-WB / SRC25ZS-W

Capacitate nominala de racire: 2.5 kW



Poze unitate interna si unitate externa



Specificatii

Unitate interna		SRK25ZS-WB		
Unitate externa		SRC25ZS-W		
Sursa de putere		Monofazic, 220 - 240, 50Hz		
Capacitate nominala de racire (Min~Max)		kW	2.5(0.9~3.1)	
Capacitate nominala de incalzire (Min~Max)		kW	3.2(0.9~4.5)	
Consumul de energie	Racire/Incalzire	kW	0.62 / 0.74	
EER/COP	Racire/Incalzire		4.03 / 4.32	
Amperaj maxim		A	9	
Nivel putere sonora	Unitate interna	Racire/Incalzire	dB(A)	50 / 53

Unitate externa	Racire/Incalzire	56 / 58		
Nivel presiune sonora	Unitate interna	Racire (Hi/Me/Lo/Ulo)	36 / 28 / 23 / 19	
		Incalzire (Hi/Me/Lo/Ulo)	39 / 30 / 24 / 19	
	Unitate externa	Racire/Incalzire	46 / 46	
Flux de aer	Unitate interna	Racire (Hi/Me/Lo/Ulo)	m ³ /min	9.9 / 8.0 / 5.9 / 5.0
		Incalzire (Hi/Me/Lo/Ulo)		11.3 / 8.7 / 6.7 / 5.9
	Unitate externa	Racire/Incalzire		27.4 / 23.6
Dimensiuni exterioare	Unitate interna	Inaltime x Latime x Adancime	mm	290 x 870 x 230
	Unitate externa			540 x 780(+62) x 290
Greutate neta	Unitate interna / Unitate externa		kg	9.5 / 31.0
Refrigerant		Tip/GWP		R32 / 675
Refrigerant		Incarcare	kg/TCO ₂ Eq	0.62 / 0.419
Dimensiuni teava refrigerant		Lichid/Gaz	ø mm	6.35(1/4") / 9.52(3/8")
Lungime teava refrigerant (o directie)			m	Max. 20
Diferente de nivel suportate		Unitate externa este mai sus/mai jos	m	Max. 10 / Max. 10
Unitate externa operating temperature range		Racire	°C	-15~46
		Incalzire		-15~24
Filtre				Filtru Antialergeni x 1, Filtru lavabil fotocatalitic si dezodorizant x 1
Clasa energetica (Racire/Incalzire)				A+++/A++
SEER				8.50
SCOP (Climat temperat)				4.70